

DUST COVER OF VACUUM CLEANER

BACKGROUND OF THE INVENTION

5 1. Field of the Invention

The present invention relates to a vacuum cleaner, and particularly to a dust cover of a vacuum cleaner capable of easily performing processes of mounting, separating and discarding a dust bag without an external contamination.

10

2. Description of the Background Art

In general, a vacuum cleaner is an apparatus which forcedly sucks dust and other contaminants with air from the outside by a suction force generated by a pressure difference between an external pressure and an internal pressure
15 of a main body which is generated by a high-speed rotation of a motor having a rotation shaft at which an impeller is mounted. Recently, among such vacuum cleaners, an upright vacuum cleaner is being widely used.

As shown in Figure 1, a vacuum cleaner according to the conventional art includes a main body 200 having a motor for generating a suction force
20 therein; and a dust suction head 100 connected with the main body 200 through a suction duct 300, and for sucking alien substances such as dust or the like from the outside by a suction force that is generated from the motor. In addition, at an upper portion of the main body 200, a handle 220 for grip of a user is

provided, and a switch 230 for switching ON/OFF the power of a vacuum cleaner ~~by ON/OFF~~ and also controlling a strength of a suction force of the vacuum cleaner, is installed.

As shown in Figures 2A to 2C, a dirt collecting chamber 400 in which a
5 dust bag 500 is disposed is provided inside the main body 200, and a dust
cover 210 for opening/closing the dirt collecting chamber 400 is mounted at the
front of the dirt collecting chamber 400. A connection duct 420 is installed inside
the dust-collecting chamber 400. The connection duct 420 communicates with
the suction duct 300, and is directly inserted into an opening 512 of the dust bag
10 500 to support the dust bag 500, and introduces air including alien substances
such as dust, which has been sucked through the suction duct 300, into the
dust bag 500.

Figures 3 and 4 illustrate a different embodiment of mounting a dust bag
500 for a conventional vacuum cleaner. As shown therein, a plate-shaped fixing
15 plate 510 is installed around an opening of the dust bag 500, and a support part
600 pivotally connected to a fixing bracket 430 installed inside the dust
collecting chamber 400 is provided. The fixing plate 510 is inserted into the
support part 600, and the support part 600 is fixed to the fixing bracket 430.
Accordingly, the dust bag 500 is interposed in the dust collecting chamber 400
20 and, at this time, its opening 512 communicates with the connection duct 420.

As shown in Figure 4, the support part 600 includes a pair of fixing
members 610 disposed so as to be isolated from each other as much as a width
of the fixing plate 510 of the dust bag 500, and whose sectional shapes are

formed in a rough 'L' shape; and a support member 620 connecting the fixing members 610 therebetween. Inside the fixing members 610, elastic ribs 641 are provided respectively to increase a fixing force of the fixing plate 510, and stopping steps 642 for restricting an insertion position of the fixing plate 501 of
5 the dust bag 500 are formed respectively. At the support member 620, a protrusion 650 that has a hinge shaft 651 inserted into a hinge hole 431 of the fixing bracket 430 is extended from the support member 620 so that the support part 600 is hingedly connected with the fixing bracket 430.

By the construction as above, when external power is applied to a motor
10 installed inside a main body 200 and thus the motor is rotated, a suction force is generated at a suction head 100 by a suction force of the motor, and air including alien substances such as dust of a floor or the like is sucked through the suction head by such a suction force and is introduced into the dust bag 500 mounted inside the dust collecting chamber 400 through the suction duct 300
15 and the connection duct 420. The alien substances such as dust included in air which have been introduced into the dust bag 500 are filtered by the dust bag, and only purged air is discharged outside the cleaner.

A vacuum cleaner according to the conventional art constructed and operating as above is disadvantageous in that an operation of a user for
20 mounting and detaching the dust bag 500 is complicated since ~~an~~the opening 512 of the dust bag 500 is directly inserted into ~~a~~the connection duct 420 installed inside ~~a~~the dust collecting chamber 400, or is interposed in the dust collecting chamber 400 through ~~a~~the special support part 600. In addition, in a

process of detaching the dust bag 500, alien substances such as dust in the dust bag 500 ~~are flowed~~flows ~~out of the dust bag 500.~~

In addition, ~~in case that~~when the dust bag 500 is installed in the dust collecting chamber 400 through the support part 600, if the fixing plate 510 is
5 not properly inserted into the support member 610 in a process of inserting the fixing plate 510 ~~of the dust bag 500~~ into the support member 610 ~~of the support part 600~~, a ~~damage of the dust bag 500~~ can be ~~generated~~damaged. And, in ~~case that~~when the dust bag 500 is separated from the dust collecting chamber 400, the support part 600 pivotally connected with the fixing bracket is pulled,
10 and then, the fixing plate 510 of the dust bag 500 is pulled out from the support part 600. Thereupon, during such operations, contaminants such as dust or the like in the dust bag 500 ~~are flowed~~flow out, and ~~hands of a user~~the user's are stained with the contaminants.

Besides, ~~in a process of~~when carrying the dust bag 500 to a place of
15 discarding after a user completely has separated the dust bag 500 from the vacuum cleaner, alien substances in the dust bag 500 ~~is flowed~~flow out through the opening 512 of the dust bag 500.

SUMMARY OF THE INVENTION

20

Therefore, an object of the present invention is to provide a dust cover of a vacuum cleaner capable of easily mounting a dust bag and capable of easily separating and discarding the dust bag without an external contamination,

by mounting a dust bag to a dust cover opening/closing a dust collecting chamber of a vacuum cleaner.

To achieve these and other advantages and in accordance with the purpose of the present invention, as embodied and broadly described herein,
5 there is provided a dust cover of a vacuum cleaner, which is installed to be separable from a dust collecting chamber so as to open/close the dust collecting chamber in which a dust bag filtering sucked dust is mounted, and having an inner portion provided with a support part to which the dust bag is mounted.

10 The foregoing and other objects, features, aspects and advantages of the present invention will become more apparent from the following detailed description of the present invention when taken in conjunction with the accompanying drawings.

15 BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are included to provide a further understanding of the invention and are incorporated in and constitute a unit of this specification, illustrate embodiments of the invention and together with the
20 description serve to explain the principles of the invention.

In the drawings:

Figure 1 is a perspective view illustrating one example of a general vacuum cleaner;

Figures 2A to 2C are partial perspective views illustrating a dust cover, a dust collecting chamber and a dust bag which are provided for a vacuum cleaner according to the conventional art;

Figure 3 is a partial perspective view illustrating a dust bag and a dust
5 collecting chamber provided for a vacuum cleaner according to the conventional art;

Figure 4 is a perspective view illustrating a support part for supporting a dust bag so that the dust bag is fixed to a dust collecting chamber provided for a vacuum cleaner according to the conventional art;

10 Figure 5 is a perspective view illustrating a disassembled vacuum cleaner according to a first embodiment of the present invention;

Figure 6 is a magnified view of a main portion of Figure 5;

Figure 7 is a perspective view illustrating a disassembled vacuum cleaner according to a second embodiment of the present invention;

15 Figure 8 is a magnified view of a main portion of Figure 7;

Figures 9A and 9B are view showing a state of operating a support part of a dust bag and a separating unit provided for a vacuum cleaner according to a second embodiment of the present invention;

Figure 10 is a perspective view illustrating a dust cover of a vacuum
20 cleaner according to a third embodiment of the present invention;

Figure 11 is a partial sectional view illustrating a vacuum cleaner according to a fourth embodiment of the present invention;

Figure 12 is a magnified view of a main portion of Figure 11;

Figure 13 is a perspective view illustrating a dust cover of a vacuum cleaner according to a fourth embodiment of the present invention; and

Figures 14A and 14B are views showing a process of separating a dust bag from a dust cover of a vacuum cleaner according to a fourth embodiment of
5 the present invention.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of
10 the present invention, examples of which are illustrated in the accompanying drawings.

As shown in Figures 5 and 6, a vacuum cleaner according to a first embodiment of the present invention includes a main body 200 having a motor (not shown) for generating a suction force therein; and a dust suction head 100
15 connected with the main body 200 through a suction duct 300, and sucking alien substances such as dust or the like from the outside by a suction force generated from the motor.

At the main body 200, there ~~are~~is provided a dust collecting chamber 400 at which a connection duct 9 communicating with the suction duct 300 is
20 installed, and in which a dust bag 500 filtering sucked dust is mounted; and a dust cover 10 separably installed at the front of the dust collecting chamber 400 so as to open/close the dust collecting chamber 400, and having a support part 20 coupled with and supporting the dust bag 500 therein.

A support plate 5 for supporting a plate-shaped-fixing plate 510 fixed to an opening 512 of the dust bag 500 is installed toward an outlet of the connection duct 9, and a duct connector 6 which is inserted into the opening 512 of the dust bag 500 in interposing the dust bag 500 is installed at one side of the support plate 5. Herein, preferably, the duct connector 6 is formed of an elastic material such as resin or the like which can be elastically deformed so as to be easily inserted into ~~an~~the opening 512 of the dust bag 500 in an ingression of the dust bag 500.

The support part 20 includes a pair of fixing members 22 disposed inside the dust cover 10 at an interval as much as a width of a fixing plate of the dust bag 500 therebetween, and having a groove 23 formed at an inner side, having a thickness as much as a thickness of the fixing plate 510 so that the fixing plate 510 is inserted therein; and a support member 24 disposed between the pair of fixing members 22, supporting the fixing members 22, and setting an insertion position of the fixing plate 510.

Preferably, at the outer surface of the dust cover 10, a handle 8 is installed so that a user can easily carry the dust cover 10.

Processes of mounting and detaching a dust bag in a vacuum cleaner according to the first embodiment of the present invention constructed as above will now be described.

In case of mounting the dust bag 500 inside the vacuum cleaner, first, a user separates the dust cover 10 from ~~at~~the main body 200 of the vacuum cleaner, and inserts the fixing plate 510 of the dust bag 500 into the groove 23

of the fixing member 22. Then, when the dust cover 10 is mounted to the main body 200, ~~at~~the duct connector 6 connected with the connection duct 9 is inserted into ~~a~~the opening 512 of the dust bag ~~400~~500, thereby ~~terminating~~finishing the process of mounting the dust bag 500. At this time, since the duct connector 6 is formed of an elastic material, the duct connector 6 moves to a predetermined position in an ingression of the dust bag 500, and then returns to an initial position, inserted into the opening 512 of the dust bag 500.

In addition, in case of separating the dust bag 500 from the vacuum cleaner and discarding the dust bag 500, a user separates the dust cover 10 from ~~a~~the main body 200 of the vacuum cleaner, ~~and then, in such a state, a user~~ moves the dust cover 10 to a place of discarding the dust bag 500, and then pulls out the fixing plate 510 of the dust bag 500 from the fixing member 22 of the support part to discard the dust bag 500, thereby ~~terminating~~finishing the process of separating and discarding the dust bag 500.

In the vacuum cleaner according to the first embodiment of the present invention as above, ~~a~~the dust bag 500 filtering alien substances such a dust is simply inserted in ~~a~~the dust cover 10 ~~opening/closing a dust collecting chamber to be installed~~, whereby a user can simply mount/separate the dust bag 500 to/from the vacuum cleaner without an external contamination.

In addition, the dust bag 500 can be carried to a place of discarding in a state that the dust bag 500 is mounted to the dust cover 100, thereby easily performing a process of separating and discarding the dust bag 500 without an

external contamination.

As shown in Figure 7, a vacuum cleaner according to a second embodiment of the present invention includes athe main body 200 having a motor for generating a suction force therein; and athe dust suction head 100
5 connected with the main body 200 through athe suction duct 300, and sucking alien substances such as dust or the like from the outside by the suction force generated from the motor.

At the main body 200, there are provided athe dust collecting chamber 400 at which athe connection duct 9 communicating with the suction duct 300 is
10 installed, and in which athe dust bag 500 filtering sucked dust is mounted; and athe dust cover 10 separably installed at the front of the dust collecting chamber 400 so as to open/close the dust collecting chamber 400, and having a support part 30 coupled with and supporting the dust bag 500 therein.

AThe support plate 5 for supporting athe plate-shaped fixing plate 510
15 fixed to athe opening 512 of the dust bag 500 is installed toward an outlet of the connection duct 9, and athe duct connector 6 which is inserted into the opening 512 of the dust bag 500 in interposing the dust bag 500 is installed at one side of the support plate 5. Herein, preferably, the duct connector 6 is formed of an elastic material such as resin or the like which can be elastically
20 deformed so as to be easily inserted into athe opening 512 of the dust bag 500 in an ingression of the dust bag 500.

The support part 30 includes a pair of fixing members 32 disposed inside the dust cover 10 at an interval as much as a width of the fixing plate 510

of the dust bag 500 therebetween, having one end pivotally installed at a hinge shaft 34 fixed to the dust cover 10, and having a groove 33 formed at an inner side, into which both sides of the fixing plate 510 of the dust bag 500 are inserted; a guide unit 40 installed at a position adjacent to the fixing member 32
5 in the dust cover 10, and for guiding an installation position of the dust bag 500; and a separating unit 50 (see Figures 9A and 9B) for separating the dust bag 500 from the dust cover 10.

As shown in Figure 8, the guide unit 40 includes a plate-shaped guide panel 42 fixed to an inner side of the dust cover 10, and having a through hole
10 44 therein; and a guide duct 46 extended from the through hole 44 toward a direction of mounting the dust bag 500, and inserted into an opening 512 of the dust bag 500 when the dust bag 500 is fixed to the fixing member 32. The through hole 44 of the guide panel 42 communicates with the duct connector 6 when the dust cover is mounted to the vacuum cleaner. Herein, preferably, the
15 guide duct 46 is formed of an elastic material such as resin or the like which can be elastically deformed so as to be easily inserted into ~~an~~the opening 512 of the dust bag 500. The guide panel 42 is fixed to an inner side of the dust cover 10 in a state that a position where the through hole 44 and the duct connector 6 communicate with each other has been preset, and the guide duct 46 is directly
20 inserted into ~~an~~the opening 512 of the dust bag 500, thereby preventing a problem that the opening 512 of the dust bag 500 and the duct connector 6 do not properly communicate with each other from occurring.

As shown in Figures 9A and 9B, the separating unit 50 includes a

connecting links 56 formed ~~32~~ near the hinge shafts 34 at a predetermined angle to the pair of fixing members 32 respectively, and integrally extended from the fixing members 32; a pressing member 54 connected with the connecting link 56 by the hinge shaft 57, and pushing the connecting links 56 to rotate the
5 pair of fixing members 32 in directions that the fixing members 32 are far away from each other; a button 52 connected with the pressing member 54 by a connecting rod 53, protruded to the outside of the dust cover 10, and receiving an external force for moving the pressing member 54; and an elastic member 58 disposed between the button 52 and the dust cover 10, and returning the
10 button 52 and the fixing member 32 to initial positions in releasing the button 52.

Preferably, at an outer surface of the dust cover 10, ~~at~~the handle 8 is installed so that a user can easily carry the dust cover 10.

Processes of mounting and separating a dust bag in a vacuum cleaner according to the second embodiment of the present invention constructed as
15 above will now be described.

~~In case~~When of mounting the dust bag 500 inside the vacuum cleaner, first a user separates the dust cover 10 from ~~at~~the main body 200 of the vacuum cleaner, applies an external force to the button 52, so that the pressing member 54 connected with the button 52 through the connecting rod 53 pushes the
20 connecting link 56. Accordingly, as shown in Figure 9B, the fixing members 32 are opened widely toward both sides. And, if the button 52 is released in a state that ~~the~~an guide duct 46 of the guide unit 40 has been inserted into an opening of the dust bag 500, as shown in Figure 9A, the button 52 and the fixing

members 32 return to their initial positions by the elastic member 58. At this time, both sides of the fixing plate 510 of the dust bag 500 are inserted into the groove 33 of the fixing member 32 to be coupled to the fixing member 32. Then, when the dust cover 10 is mounted to the main body 200, the duct connector 6
5 connected with the connection duct 9 is inserted into the through hole 44 of the guide panel 42, thereby terminating the process of mounting the dust cover 500. At this time, the duct connector ~~56~~ is formed of an elastic material, so that the duct connector 6 moves to a predetermined position in an ingression of the guide panel 42 and returns to an initial position to be inserted into the opening
10 512 of the dust bag 500.

In addition, ~~in case of~~when separating the dust bag 500 from the vacuum cleaner and discarding, a user separates the dust cover 10 from the main body 200 of the vacuum cleaner, ~~and then, in such a state, a user~~ moves the dust cover 10 to a position of discarding the dust bag 500, and then applies
15 an external force to the button 52. Thus, as shown in Figure 9B, the pressing member 54 pushes the connecting link 56 to widely open the fixing members 32 toward both sides. At this time, both sides of the fixing plate 510 of the dust bag 500 ~~are slipped~~slip out from the groove 33 of the fixing member 32, and thus the dust bag 500 falls off by self-weight, thereby ~~terminating~~finishing the
20 process of separating and discarding.

In the vacuum cleaner according to the second embodiment of the present invention as above, atthe dust bag 500 filtering alien substances such as dust or the like is simply installed at atthe dust cover 10 ~~opening/closing a~~

dust-collecting-chamber 400, whereby a user can easily mount the dust bag 500 to the vacuum cleaner, and can separate and discard the dust bag 500 without an external contamination.

In addition, ~~a~~the guide unit 40 for guiding an installation position of the dust bag 500 is provided, whereby the dust bag 500 and the duct connector 6 can properly communicate with each other without a problem.

Besides, ~~since a~~because the separating unit 50 for separating the dust bag 500 is provided, a user has no need to remove the dust bag 500 at firsthand in discarding the dust bag 500, thereby preventing a problem that a ~~hand of a user~~the user's hand is stained with contaminants in removing the dust bag 500.

A vacuum cleaner according to a third embodiment of the present invention will now be described with reference to Figure 10. Hereinafter, the same numerals will be given to the same parts as those in abovementioned embodiments and explanations thereof will be omitted.

The vacuum cleaner according to the third embodiment of the present invention is similar to the abovementioned second embodiment. But, in the vacuum cleaner according to the third embodiment, a groove 133 formed in a fixing member 132 of a support part 130 provided in ~~a~~the dust cover 10 is formed to be vertically long. A fixing plate of the dust bag 500 is fixed thereto in a state of having been inserted into the groove 133, and the fixing plate 510 is not separated from the groove 133 by an elastic force of the abovementioned elastic member 58.

In the vacuum cleaner according to the third embodiment of the present invention, processes of mounting and separating the dust bag 500 and effect of the invention are the same as those explained in the abovementioned embodiments.

5 As shown in Figures 11 and 12, a vacuum cleaner according to a fourth embodiment of the present invention includes athe main body 200 having a motor for generating a suction force therein; and athe dust suction head 100 connected with the main body 200 through athe suction duct 300, and sucking alien substances such as dust or the like from the outside by a suction force
10 generated from the motor.

At the main body, there are provided athe dust collecting chamber 400 in which athe dust bag 500 filtering sucked dust is mounted; and a dust cover 110 separably installed at the front of the dust collecting chamber 400 so as to open/close the dust collecting chamber 400.

15 The dust cover 110 is provided with a connection duct 109 communicating with the suction duct 300; a support part 120 coupled with and supporting the dust bag 500; and a separating unit 150 for separating the dust bag 500 from the dust cover.

The connection duct 109 is integrally fixed to the inside of the dust cover
20 110, and is inserted into an outlet of the suction duct 300 continued to the inside of the main body 200 when the dust cover 110 is mounted to the vacuum cleaner. Preferably, the dust cover 110 and the connection duct 109 are formed of a transparent material so that a user can observe a state of sucking dust with

the naked eye.

The supporting unit 120 is composed of a tubular duct connector 106 fixed toward an outlet of the connection duct 109, formed of an elastic material such as resin having an elastic force, and having a support step 107 protruded
5 at the middle thereof in a radial direction. Since the duct connector 106 is formed of an elastic material, when the opening 512 of the dust bag 500 is inserted thereto, the support step 107 is depressed by a force of inserting the dust bag 500. After the opening 512 has been completely inserted thereto, the support step 107 returns to an initial state, so that the opening 512 is not
10 released from the duct connector 106.

The separating unit 150 includes a lever 156; and a knob 152 mounted at one end of the lever 156, and to which an external force is applied by a user. Herein, one end of the lever 156 is protruded to the outside of the dust cover 110, its middle portion is bent, and the bent portion is hingedly connected to the
15 dust cover 110 by a hinge shaft fixed to the dust cover 110. Also, the other end of the lever 156 is positioned at the front of the dust bag 500.

As shown in Figure 13, the other end of the lever 156 is divided at a position adjacent to the duct connector 106 as much as a width of the fixing plate 510, so that the dust bag 500 can be more effectively removed.

20 As shown in Figures 14A and 14B, in the separating unit 150, when an external force is transmitted to the knob 152 (downward on the drawing), the lever 156 is rotated centering on the hinge shaft 134, and thus the other end of the lever 156 pushes a fixing plate 510 of the dust bag 500 to separate the dust

bag 500 from the duct connector 106. When the dust bag 500 is inserted
thereinto, the knob 152 and the lever 156 can return to initial positions by being
pushed by the fixing plate 510 of the dust bag 500. Besides, by installing an
elastic member 158 between the lever 156 and the dust cover 110, the lever
5 156 and the knob 152 can return to initial positions automatically by the elastic
member 158 in releasing the lever 156.

Preferably, a handle 108 is installed at an outer surface of the dust cover
110 so that a user can easily carry the dust cover 110.

Processes of mounting and separating a dust bag in a vacuum cleaner
10 according to the fourth embodiment of the present invention constructed as
above will now be described.

~~In case of~~When mounting the dust bag 500 inside the vacuum cleaner,
first, a user separates the dust cover 110 from a main body 200 of the vacuum
cleaner, and inserts an opening 512 of the dust bag 500 into the duct connector
15 106. Then, the dust cover 110 is mounted to the main body 200, thereby
~~terminating~~finishing the process of mounting the dust bag 500. At this time, the
connection duct 109 is inserted into an outlet of the suction duct 300 to
communicate with the suction duct.

In addition, ~~in case of~~when separating the dust bag 500 from the
20 vacuum cleaner and ~~discarding the dust bag 500~~, a user separates the dust
cover 110 from the main body 200 of the vacuum cleaner, ~~and then, in such a~~
~~state, a user~~ moves the dust cover 110 to a place of discarding the dust bag 500,
and then applies an external force to the knob 152. Then, the lever 156 rotates

centering on the hinge shaft 134, and thus, the other end of the lever 156 pushes the fixing plate 510 of the dust bag 500, so that the dust bag 500 falls off by self-weight, thereby terminating the process of separating and disposing.

In the vacuum cleaner according to the fourth embodiment of the present invention, ~~since~~ because the dust bag 500 filtering alien substances such as dust is simply installed to the dust cover 110 ~~opening/closing a dust collecting chamber 400~~, a user can easily mount the dust bag 500 to the vacuum cleaner, and can separate and discard the dust bag 500 without an external contamination. In addition, ~~since~~ because the separating unit 150 for separating the dust bag 500 is provided, a user has no need to manually remove the dust bag 500 ~~at firsthand in discarding the dust bag 500~~ thereby preventing a problem that ~~a hand of a user~~ the user's hand is stained with alien substances such as dust in removing the dust bag 500.

In addition, in the vacuum cleaner according to the fourth embodiment of the present invention, the connection duct 106 which is connected with the suction duct 300 is integrally fixed to the dust cover 110, and the dust bag 500 is directly coupled and supported toward the outlet of the connection duct. Accordingly, unlike the conventional art, the process of coupling the dust bag 500 to the dust cover 110 and then fitting an opening 512 of the dust bag 500 to the outlet of the connection duct 106 is omitted, thereby further simplifying a process of mounting the dust bag 500.

As the present invention may be embodied in several forms without departing from the spirit or essential characteristics thereof, it should also be

understood that the above-described embodiments are not limited by any of the details of the foregoing description, unless otherwise specified, but rather should be construed broadly within its spirit and scope as defined in the appended claims, and therefore all changes and modifications that fall within
5 the metes and bounds of the claims, or equivalence of such metes and bounds are therefore intended to be embraced by the appended claims.